

oznaczenia przyłączy wymienników lutowanych serii "O"

Typ:	oznaczenie przyłącza								
ParaBrazed	EE	AE	AI	AT	BE	CE	DE	FE	GE
O...C12	-	3/4"	3/4"	-	-	-	-	-	-
O...C15	-	3/4"	-	-	18mm	3/4" - 16mm (5/8")	-	-	-
O...C30	3/4"	1"	-	1"	-	1" - 22mm (7/8")	1/2"	-	3/4" - 18mm
O...C35	1"	1 1/4"	-	-	-	1 1/4" - 35mm (1 3/8")	-	-	-
O...C60	1"	1 1/4"	-	-	-	1 1/4" - 35mm (1 3/8")	-	-	-
O...C70	-	1 1/2"	2"	-	-	1 1/2" - 41mm (1 5/8")	-	-	-
O...C85	-	2"	-	-	60,8mm	2" - 54mm (2 1/8")	-	DN50	-
O...C100	-	2 1/2"	-	-	-	2 1/2" - 67mm (2 5/8")	-	-	-
O...C300	-	-	-	-	-	DN100 - DN65	-	DN100 - DN65	-

wymiary wymienników lutowanych APV serii "O"

Typ:	B	H	b	h/h	D	L	waga pustego wymiennika	pojemność 1 kanału
	mm	mm	mm	mm	mm	mm	kg	Ltr
O...12	73	189	40	154	20	7+(2,2xN)	0,68+(0,045xN)	0,0164
O...15	73	202	42	172	26	7+(2,3xN)	0,7+(0,044xN)	0,0260
O...30	106	306	50	250	28	7+(2,2xN)	1,61+(0,091xN)	0,0520
O...35	124	337	69	281	28	7+(2,3xN)	2,7+(0,16xN)	0,0790
O...60	124	532	69	476	19,5	7,5+(2,3xN)	3,5+(0,2xN)	0,1260
O...70	152	452	72	372	50	9+(2,35xN)	4,72+(0,24xN)	0,1700
O...85	271	532	198	460	50	7+(2,3xN)	7+(0,42xN)	0,2830
O...100	184	605	92	520	50	7+(2,4xN)	7,2+(0,42xN)	0,2030
O...300	362	987	214	860/815	90	18+(2,8xN)	52,5+(1,26xN)	0,6600

